



适用范围 The scope of application	适用于易燃易爆的环境中走道内或海上石油平台做投光照明用。 Provide the illumination for the passage in the flammable and explosive environment or sea oil platform.	
型号 Type	CFD13	
防爆标志 Explosion-proof mark	Ex de IIC T6 Gb	
额定电压 Rated voltage	AC100-240V 50/60Hz	
功率 Power	50W	80W
功率因数 Power factor	≥0.9	
光源 Illuminant	LED	
光源颜色 Illuminant color	白 White	
光源寿命 Illuminant life	≥50000h	
光通量 Luminous flux	5000lm	
显色指数 RA	Ra ≥70	
色温 Color temperature	4000K-6500K	
防护等级 Protection class	IP66	
电缆外径 Cable diameter	Ø10~Ø12	
安装方式 Installation	吸顶式, 吊杆式, 壁式, 法兰式 Ceiling type, Pendant type, Wall type, Flange type	
环境温度 Ambient temperature	-20℃ ~ +45℃	
灯体材质 Light body material	航空铝 Aviation aluminium	
灯罩材质 Shade material	钢化玻璃 Toughened glass	
重量 Weight	7.5Kg	
备注 Remarks	可选配G3/4管接头 G3/4 pipe joint is optional.	