



适用范围 The scope of application	适用于各类船舶有滴水、溅水和凝水的场所，如机炉舱、干货舱、轴隧、管弄、露天甲板等场所作照明之用； Applied to illumination of water dripping, water spattering, water coagulating place in ships, such as oven cabin, dry cabin, tunnel, pipeline and weather deck etc.		
型号 Type	HJCL16	HJCL16-E	
型谱型号 Military Type	LC3C / 120L	LC3F / 120L	
额定电压 Rated voltage	AC100~240V 50/60Hz	AC100~240V 50/60Hz	DC24V
功率 Power	24W	24W	3W
功率因数 Power factor	≥0.9		
光源 Illuminant	LED		
光源颜色 Illuminant color	白 White		
光源寿命 Illuminant life	≥ 50000h		
光通量 Luminous flux	2400lm	2400lm	300lm
显色指数 RA	Ra ≥ 85		
色温 Color temperature	3000K~6500K		
防护等级 Protection class	IP66		
电缆外径 Cable diameter	Ø10~Ø14		
安装方式 Installation	吸顶式 Ceiling type, 侧装式 Side mounting type, 壁挂式 Wall mounting type, 立杆式 Vertical stick type		
环境温度 Ambient temperature	-30℃ ~ +55℃		
灯体材质 Light body material	钢, 不锈钢 Steel, Stainless steel		
灯罩材质 Shade material	PC		
灯罩颜色 Lamp shade color	乳白色 Milky white		
重量 Weight	2.6Kg	2.8Kg	